



Performance. Power.  
Productivity.™

# DFPXP


## 20ga. 1/2" Crown Clinching Stapler

The DFPXP is a compact, lightweight, yet powerful clinch stapler. It is designed with high quality components for dependable all-day use in industrial applications.



### Specifications

Item #	8H0001N
UPC	741474095535
Mode of Operation	Sequential Actuation
Reg. Operating Pressure	65-100 psi (4 - 7 bar)
Air Inlet	1/4" NPT
Tool Weight	4.9 lbs (2.24 kg)
Height	12.9" (327 mm)
Length	14.9" (380 mm)
Width	3.0" (75 mm)
Throat Depth	6.9" (175 mm)
Fastener Capacity	230



### Fastener Specifications

Gauge	20
Crown	1/2" (12.7 mm)
Length	5/16" - 5/8" (8mm - 16mm)
Finish	Galv.
Collation	Glued Strip

### Applications

Corrugated box fabrication, light assembly and packaging, shoe making.

### Features and Benefits

- High capacity magazine holds 230 staples – less reloading means maximum production
- Tool-free adjustable anvil opening
- Rubber comfort grip reduces vibration, slipping, and fatigue
- Bottom-load magazine for quick reloading
- 6.9" throat allows for extended reach into cartons
- 5 year limited warranty

### SENCO® 20 Ga. 1/2" Crown Fine Wire

Length	Item Code	Carton Count	Point	Finish	Coating
3/16"	F05BAAP	24.M	Chisel	Galv	Plain
3/8"	F06BAA	10.M	Chisel	Galv	Plain
3/8"	F06BAAP	24.M	Chisel	Galv	Plain
1/2"	F08BAAN	10.M	Chisel	Galv	Plain
1/2"	F08BAAP	10.M	Chisel	Galv	Plain
3/8"	F06BGA	10.M	Chisel	Stainless	Plain
1/2"	F08BGA	10.M	Chisel	Stainless	Plain

**Contact Actuation Trigger** (also known as dual action, bounce or bottom fire) operates in the following sequence- pull the trigger first and keep the trigger pulled while moving the tool along the work surface with a bouncing motion, depressing the safety element at the nose of the tool against the work surface where the fastener is to be driven. This trigger is recommended for use by trained professionals only in high production or volume applications.

**Sequential Actuation Trigger** (also known as restrictive trigger or trigger fire) operates in the following sequence - depress the safety element at the nose of tool against the work surface then pull the trigger. After each fastener is driven, release the trigger and lift the tool off the work surface before starting the sequence again. This trigger is recommended and acceptable for most applications.

For additional information on how SENCO will save you time, reduce costs, and increase quality, call us at 1-800-543-4596 to find your nearest Authorized Senco Dealer or Distributor or visit our web site at: [www.senco.com](http://www.senco.com)